

DURABLE. RELIABLE. DEPENDABLE.

GPM Eliminator™
SOLID PUMPING SOLUTIONS

**HEAVY-DUTY VERTICAL
HYDRAULIC EVEN WEAR
SLURRY PUMP**

**HYEW
SERIES**

SPECIFICATIONS

FEATURES

- Heavy duty closed impeller for pumping abrasive solids.
- 28% High Chrome 650+ Brinell hardness assures long life of impeller, wear plate and casing.
- Double mechanical seal with Silicon Carbide vs. Silicon Carbide seal faces running in a barrier fluid for lubrication and cooling.
- Extended dry run capabilities. Minimizes the cost of operation.



SPECIFICATIONS

Horsepower
Discharge Size
Performance Range
Capacity
Head
Max Particle Size
Motor Nomenclature
Type / Speed / HZ
Maximum Water Temperature
Operation Mode
Materials of Construction
Casing
Impeller
Wear Plate
Shaft
Bearing Housing
Fasteners
Impeller Type
Mechanical Seal
Seal Faces
Elastomers
Labyrinth Seal
Lubrication
Bearings
Thrust
Radial
Lubrication
Accessories

STANDARD

15 - 800 HP
3" – 8"
250 - 6000 US GPM
50' – 350' TH
3 1/4
Hydraulic / Variable 350 to 2200 RPM / 60 HZ
200° F
Hydraulic Driver
28% High Chrome 650+ Brinell Hardness
28% High Chrome 650+ Brinell Hardness
28% High Chrome 650+ Brinell Hardness
416 Stainless Steel
Cast Iron 3/8" Minimum Thickness
18-8 Stainless Steel
Enclosed
Silicon Carbide
Viton
Stainless Steel/Cast Steel
Mobil / Synturion 6
Double Angular Contact
Deep Groove Ball Bearing
Permanently Lubricated with Mobil SHC Polyrex 222
Agitators / Discharge Hose / Variable Speed / Urethane Coating / Elbows in Steel or High Chrome / Control Panels / Moisture and Thermal Protection / Rafts

**Best used in applications
such as barges and remote
ponds without electricity.**

GPM
SOLUTIONS DRIVEN