DURABLE, RELIABLE, DEPENDABLE.



HEAVY-DUTY STANDARD HORIZONTAL LOW HEAD SLURRY PUMP

SHLH SERIES

SPECIFICATIONS

FEATURES

- Adjustable wear plate increases wear life when pumpage contains heavy abrasive particles.
- 28% High Chrome 650+ Brinell hardness assures long life of impeller, wear plate and casing.
- Double mechanical seal with Silicon Carbide vs. Silicon Carbide seal faces running in a barrier fluid for lubrication and cooling.
- Large Diameter shafts to increase seal and bearing life with minimal deflection.
- Inverter-duty TEFC, severe service, low voltage motor minimizes cost of operation.



If you have problems with packing and sealing water, this pump will solve all your problems.

SPECIFICATIONS

STANDARD

Horsepower 15-500 HP Discharge Size 3"-8"

Capacity 100 - 6250 US GPM
Head 10' - 140' TH

Max Particle Size 4-1/2"

Type / Speed / HZ TEFC Air-Filled / 900 to 1800 RPM / 60 HZ

Voltage / Phase 230, 460, 575 V / 3 Phase

Service Factor 1.15

Insulation Class F

Maximum Water Temperature

Operation Mode

Shaft

Motor Nomenclature

Materials of Construction

Casing 28% High Chrome 650+ Brinell

Hardness

Impeller 28% High Chrome 650+ Brinell

Hardness

180° F

Synchronous Speed or V.F.D.

Wear Plate 28% High Chrome 650+ Brinell

Hardness

416 Stainless Steel

Bearing Housing Cast Iron

Fasteners 18-8 Stainless Steel

SPECIFICATIONS

Impeller Type Mechanical Seal

Seal Faces
Elastomers
Labyrinth Seal
Lubrication

Bearings

Thrust

Radial Lubrication

Accessories

STANDARD

Semi-Open

Silicon Carbide Viton

Ctalala

Stainless Steel/Cast Steel Mobil / Synturion 6

Double Angular Contact

Deep Groove Ball Bearing Permanently Lubricated with Mobil SHC Polyrex 222

Agitators / Discharge Hose / Variable Speed / Urethane Coating / Elbows in Steel or High Chrome / Control Panels / Moisture and Thermal Protection / Rafts

